


小尺寸超高频抗金属标签

SMALL SIZE UHF ON METAL RFID TAGS

产品照片 Graph	型号 Type	材质/尺寸(长x宽x厚) Mat'l/Size (LxWxT)	芯片 Chip EPC/User(bits)	频率、手持机读 距 Freq(MHz)/ Read Range	使用/保存温度 Application/ Storage temp	安装方式 Attachment
	PT05	PCB 5mm (Dia), 3mm(T)	Ucode8 128/ 0	902~928 0.25m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT0904	PCB 9.3x 4.3x1.6 mm	Ucode7M 128/32	902~928 0.25m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT1005	PCB 10x5 x3 mm	Ucode8 128/ 0	902~928 0.45m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT1010	PCB 10mm(Dia), 2mm(T) 10mm(Dia), 3mm(T)	M4QT 128/ 512 Ucode8 128/ 0	902~928 0.45m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT1207	PCB 12x 7x 3 mm	Ucode8 128/ 0 M4QT 128/ 512	902~928 0.70m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT1309	PCB 13x 9x 3 mm	Ucode8 128/ 0 M4QT 128/ 512	902~928 0.85m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT1809	PCB 18x 9x 3 mm 18x 9x 2 mm	M4QT 128/ 512 Ucode8 128/ 0	902~928 0.60m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT2208	PCB 22 x 8 x 2 mm	Ucode7M 128/ 32	902~928 1m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT2309	PCB 23 x 9 x 3.4 mm	Ucode8 128/ 0	902~928 1.3m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT1010	陶瓷 Ceramic 10mm(Dia), 1.8mm(T)	H3 96/ 512 Ucode8 128/ 0	902~928 1.3m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT1309	陶瓷 Ceramic 13 x 9 x 3 mm	H3 96/ 512 Ucode8 128/ 0	902~928 1.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT1616	陶瓷 Ceramic 16mm(Dia), 2mm(T)	H3 96/ 512 Ucode8 128/ 0	902~928 1.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT1909	陶瓷 Ceramic 19 x 9 x 3 mm	H3 96/ 512 Ucode8 128/ 0	902~928 1.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT2117	陶瓷 Ceramic 21 x 17 x 2 mm	H3 96/ 512 Ucode8 128/ 0	902~928 2.1m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT2509	陶瓷 Ceramic 25 x 9 x 3 mm	H3 96/ 512 Ucode8 128/ 0	902~928 4m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	CT2525	陶瓷 Ceramic 25 x 25 x 3 mm	H3 96/ 512 Ucode8 128/ 0	902~928 5m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker

1. 产品读距在用不同的读写器及不同的环境下会有差异 (Might be of different read range by different readers and applications)。
2. 以上清单并没有包含公司所有类似的小尺寸产品，有需求请联系业务深圳市鸿顺捷电子有限公司 (The above list does not include all the small size products of HSJ, if needed, please contact with HSJ)。
3. 小尺寸标签有欧标可选，部分有多种芯片可选 (Can choose ETSI, FCC types, can choose other chips)。
4. 能定制各种尺寸及采用不同芯片的标签 (Can customize tags)。

超高频抗金属标签

UHF ON METAL RFID TAGS

产品照片 Graph	型号 Type	材质/尺寸(长x宽x厚) Mat'l /Size (LxWxT)	芯片 Chip EPC/User(bits)	频率、手持机读 距 Freq(MHz)/ Read Range	使用/保存温度 Application/ Storage temp	安装方式 Attachment
	PT3613	PCB 36x 13x 3mm	M4QT 128/ 512 Ucode8 128/ 0	902~928 M4QT: 1.1m Ucode8: 1.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT5010	PCB 50x 10x 3mm	Ucode8 128/ 0	902~928 1.5m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT5313	PCB 53x 13x 3.4mm	M4QT 128/ 512	902~928 1.55m	-25℃~ 75℃ -40℃~ 110℃	粘贴 Sticker
	PT6025	PCB 60x 25x 3.4mm	M4QT 128/ 512	902~928 2m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT7020	PCB 70x 20x 3.4mm 70x 20x 3.0mm	M4QT 128/ 496 Ucode8 128/ 0	902~928 2m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT8020	PCB 80x 20x 3.4mm 80x 20x 3.0mm	M4QT 128/ 512 Ucode8 128/ 0	902~928 2.2m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT8530	PCB 85x 30x 3.4mm	QSTAR 496/1496 H3 96/ 512	902~928 1.8m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT8554	PCB 85x 54x 3.4mm	QSTAR 496/1496 H3 96/ 512	902~928 4m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT9011	PCB 90x 11x 3.4mm	M4QT 128/ 512	902~928 1.8m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT9522	PCB 95x 22x 3mm	H3 96/ 512	902~928 3.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT9525	PCB 95x 25x 3.4mm 95x 25x 3.0mm	M4QT 128/ 512 Ucode8 128/ 0	902~928 3.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT10030	PCB 100x 30x 3.4mm	H3 96/ 512	902~928 3.7m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet
	PT11220	PCB 112x 20x 3 (T)mm	H3 96/ 512	902~928 4m	-25℃~ 75℃ -40℃~ 110℃	粘贴、螺丝或 铆钉 Sticker/ screw/ rivet

1. 产品读距在用不同的读写器及不同的环境下会有差异 (Might be of different read range by different readers and applications)。
2. 以上清单并没有包含公司所有类似的尺寸的产品, 有需求请联系业务人员 (The above list does not include all similar size products of HSJ, if needed, please contact with HSJ)。