


软质超高频抗金属标签

SOFT UHF ON METAL RFID TAGS

产品照片 Graph	型号 Type	材质/尺寸(长x宽x厚) Mat'l /Size (LxWxT)	芯片 Chip EPC/User(bits)	频率、手持机读 距 Freq(MHz)/ Read Range	使用/保存温度 Application/ Storage temp	安装方式 Attachment
	LP10325	PET 103x 25x 1.7mm	M4QT 128/ 512 Ucode7XM+2K 448/2048	902~928 3.5m	-25℃~ 70℃ -35℃~ 70℃	粘贴 Sticker
	LP 7325	PET 73x 25 x 1.7mm	M4QT 128/ 512 Ucode7XM+2K 448/2048	902~928 2.4m	-25℃~ 70℃ -35℃~ 70℃	粘贴 Sticker
	LP 6025	PET 60x 25x 1.7mm	M4QT 128/ 512 Ucode7XM+2K 448/2048	902~928 2m	-25℃~ 70℃ -35℃~ 70℃	粘贴 Sticker
	Printable On metal tags (可打印抗金 属标签)	PET 不同尺寸, 可支持所有 RFID 打印机 Different sizes, can be printed by all RFID printers	R6 128/0	902~928 不同尺寸不同 读距	-25℃~ 70℃ -30℃~ 70℃	粘贴 Sticker

能根据客户要求进行产品定制 (Can customize printable on metal tags)